

PHOTOMETRIC TEST REPORT

NOMAD MARKER

astro

LIGHT EFFICIENCY:

17 Lumen/Watt

LIGHT QUALITY:

CRI: 92.5

COLOR TEMPERATURE:


2772 K

OUTPUT: 109 lm

PEAK: 74.3 cd

POWER: 6.3 W


PF: 0.88




Tracking number: [n/a](#)

Product name:
Nomad Marker
Item number:


Date and time:
08/01/2026 16:25:48
Description:





SPECTRA



POWER





COLOR DETAILS



TM30: 92.9

CRI: 92.5 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
92.4	95.8	98.8	94.0	92.5	96.5	91.4	78.9	52.2	90.0	96.2	87.7	93.3	98.5	86.3


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
90.1	92.0	91.0	95.1	96.4	96.1	94.0	98.4	96.3	94.6	92.9	90.9	91.1	88.1	91.4	86.8

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
86.0	95.0	92.2	92.5	92.8	92.3	93.1	94.2	96.8	94.9	93.8	93.3	92.5	84.3	84.9

CQS: 90.9



COLOR PARAMETERS

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2772 K	92.5	52.2	92.9	98.8	90.9	0.457	0.414	0.259	0.352	0.0016







Rf 92.9

Fidelity index Rf


Rg 98.8

Gammut index Rg

Hue Bin	Rf	Graphic shifts (%)	
		Chroma	Hue
1	90	-6%	-1%
2	92	-4%	3%
3	91	-2%	4%
4	95	0%	2%
5	96	1%	3%
6	96	2%	0%
7	94	-1%	-3%
8	98	0%	-1%
9	96	-2%	0%
10	95	-2%	3%
11	93	0%	5%
12	91	4%	-1%
13	91	3%	-6%
14	88	2%	-10%
15	91	-1%	-5%
16	87	-4%	-9%



BEAM DETAILS



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
74lx	19lx	8lx	5lx	3lx	2lx	2lx	1lx	1lx	1lx	1lx	1lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx
6.9fcd	1.7fcd	0.8fcd	0.4fcd	0.3fcd	0.2fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
74.1	73.4	71.4	68.0	63.3	57.6	51.0	44.0	36.9	30.2	24.3	19.1	14.5	10.7	7.4	4.5	2.0	0.2	0.0	0.0
100%	99%	96%	92%	85%	78%	69%	59%	50%	41%	33%	26%	20%	14%	10%	6%	3%	0%	0%	0%

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
74.1	72.6	68.1	60.4	51.0	41.8	34.3	28.4	23.5	19.3	15.2	11.5	8.2	5.3	2.7	0.2	0.0	0.0	0.0	0.0
100%	98%	92%	81%	69%	56%	46%	38%	32%	26%	20%	16%	11%	7%	4%	0%	0%	0%	0%	0%

Intensities in 180° c-plane


0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
74.1	73.7	71.9	68.8	64.4	58.8	52.0	44.4	36.9	29.9	23.7	18.3	13.6	9.7	6.4	3.5	1.2	0.0	0.0	0.0
100%	99%	97%	93%	87%	79%	70%	60%	50%	40%	32%	25%	18%	13%	9%	5%	2%	0%	0%	0%

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
74.1	72.4	68.3	61.6	52.8	43.0	33.5	26.0	20.4	16.5	13.1	10.3	7.8	5.4	3.2	1.2	0.0	0.0	0.0	0.0
100%	98%	92%	83%	71%	58%	45%	35%	28%	22%	18%	14%	11%	7%	4%	2%	0%	0%	0%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
66.2°	129.1°	151.3°	90.8%	71.8%


ISO CANDELA DIAGRAM



10%	7 cd
20%	15 cd
30%	22 cd
40%	30 cd
50%	37 cd
60%	44 cd
70%	52 cd
80%	59 cd
90%	67 cd

Conditions:
Number of c-planes: 8
Candela at center: 74 cd

ISO LUX DIAGRAM



3%	22.2m lx
5%	37.1m lx
10%	74.1m lx
30%	0.222 lx
50%	{LUX_10M50} lx

Conditions:
Number of c-planes: 8
Lux at center: 0.741 lx

Lux distribution on a surface
when lamp is mounted at 10
meters from the surface.

Mounting height: 10 meters (33 feet)

GLARE EVALUATION ACCORDING TO UGR


UGR data could not be calculated due to missing/wrong symmetry. Go to Edit -> Photometric -> Corrections and select Correct asymmetry (UGR not defined for asymmetrical distributions)..

COEFFICIENTS OF UTILIZATION

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	108	104	101	109	105	102	100	101	99	97	97	95	94	94	92	91	89
2	103	97	91	87	101	95	90	86	91	87	84	88	85	82	85	83	80	78
3	96	87	81	75	94	86	80	75	83	78	73	80	76	72	78	74	71	69
4	89	79	72	66	87	78	71	66	75	69	65	73	68	64	71	67	63	61
5	83	72	64	59	81	71	64	58	69	63	58	67	62	57	65	61	57	55
6	77	66	58	53	76	65	58	53	63	57	52	62	56	52	60	55	51	49
7	73	61	53	48	71	60	53	48	59	52	47	57	51	47	56	51	47	45
8	68	56	49	44	67	56	48	43	54	48	43	53	47	43	52	47	43	41
9	64	52	45	40	63	52	45	40	51	44	40	50	44	40	49	43	39	38
10	61	49	42	37	59	48	41	37	47	41	37	46	41	37	46	40	36	35

LAMPS (number of lamps)

LUMINAIRE BUDGETARY DIAGRAM



ZONAL LUMEN SUMMARY


0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
6.87 lm	18.0 lm	22.7 lm	21.5 lm	17.6 lm	12.6 lm	7.30 lm	2.43 lm	0.115 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0.000 lm	0.006 lm	0.014 lm	0.021 lm	0.033 lm	0.036 lm	0.035 lm	0.023 lm	0.008 lm

FLICKER


FLICKER CURVE (COMPLETE SAMPLED)



FLICKER FRAME (FRAME OF ONE FLICKER)



FLICKER FFT (FREQUENCY SCOPE OF FLICKER)



FLICKER RESULTS:

Flicker frequency:	87.34 Hz
Flicker index:	0
Flicker percentage:	0.13 %
SVM: (Visual flicker)	0

FLICKER CONDITIONS:

Sample rate:	20000 samples/second
--------------	----------------------