CALVI WALL 305

GENERAL

LOCATION: CLASS: LOCATION RATING: VOLTAGE: INSTALLATION ORIENTATION: FITTING METHOD: MAIN MATERIAL: DIMENSIONS:

CUT OUT HOLE: RECESS DEPTH: FIRE RATING: CABLE LENGTH: GROSS WEIGHT: ADA COMPLIANT: IC RATING:

LAMP

LIGHT SOURCE: MAXIMUM WATTAGE: LAMP INCLUDED: MAXIMUM LAMP LENGTH: R9: MACADAM ELLIPSE: TILT ADJUSTABLE ANGLE: ROTATION ADJUSTABLE ANGLE: AVERAGE LIFESPAN: L70: BEAM ANGLE:

ELECTRICAL

SWITCHED: DIMMABLE: DIMMING METHOD: DRIVER INCLUDED: DRIVER OUTPUT CURRENT: DRIVER OUTPUT VOLTAGE: SUPPLY FREQUENCY: DRIVER/BALLAST VOLTAGE: DRIVER AVERAGE LIFESPAN: EFFICACY: Exterior cETLus (Class 1) Wet Mains 120V Wall Mount 4″ Octagon Box Metal - 304 Stainless Steel H: 386mm W: 226mm D: 280mm H: 15.20″ W: 8.90″ D: 11.02″

Not Applicable Not Applicable Not Applicable 11.07lbs No Not Applicable

E26/MEDIUM 60W MAX No 200mm Not Applicable Not Applicable Not Applicable Lamp Dependent Not Applicable Not Applicable

No Yes Lamp Dependent Not Applicable Not Applicable Not Applicable Not Applicable Not Applicable Not Applicable

ADDITIONAL INFORMATION

SHADE INCLUDED SHADE MATERIAL

Not Applicable Not Applicable



CODE: 1306007 (8146) FINISH: POLISHED NICKEL



CODE: 1306008 (8147) FINISH: TEXTURED BLACK



CODE: 1306009 (8148) FINISH: ANTIQUE BRASS

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

astro

PRODUCT ELEVATIONS



Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.









