FUSE 3 (CORD SET)

astro

GENERAL

LOCATION: Interior/Headboard Installation Only

CLASS: cULus (Class 1)

LOCATION RATING: Dry

DRIVER REQUIRED: Mains 120V INSTALLATION ORIENTATION: Wall Mount

FITTING METHOD: Included Junction Box

MAIN MATERIAL: Metal

DIMENSIONS (mm): H: 200 W: 75 D: 92

DIMENSIONS (inch): H: 7.9 W: 3.0 D: 3.6

CUT OUT HOLE (mm/inch): L: 180 W: 58/L: 7.1 W: 2.3

RECESS DEPTH (mm/inch): 60/2.4 FIRE RATING: -

CABLE LENGTH (mm/inch): 3050/120
GROSS WEIGHT (lb): 2.1
ADA COMPLIANT: Yes
IC RATING: IC Rated

LAMP

LIGHT SOURCE: High Power LED

WATTAGE: 2W

LAMP INCLUDED: Yes (Integral)

MAXIMUM LAMP LENGTH (mm/inch): LUMINOUS FLUX (Im): 185 COLOUR TEMP (K): 2700 CRI (Ra): 80 MACADAM ELLIPSE: 3-Step TILT ADJUSTABLE ANGLE (°): 90 ROTATION ADJUSTABLE ANGLE (°): 330 LIFETIME (hrs): 60000 BEAM ANGLE (°): 18

FL FCTRICAL

SWITCHED: Yes

DIMMABLE: No

DIMMING METHOD:

SUPPLY FREQUENCY (Hz): 50-60

DRIVER/BALLAST VOLTAGE (V): 100-277

DRIVER LIFETIME (hrs): 30000

EFFICACY (Im/W): 57

ADDITIONAL INFORMATION:

SHADE INCLUDED: SHADE/DIFFUSER MATERIAL: SHADE/DIFFUSER FINISH -

F MARK: Suitable for mounting on flammable materials



CODE: 1215110 FINISH: MATT WHITE



CODE: 1215111 FINISH: MATT BLACK



CODE: 1215112 FINISH: POLISHED CHROME



CODE: 1215113 FINISH: MATT NICKEL



CODE: 1215114 FINISH: MATT GOLD



CODE: 1215115 FINISH: BRONZE

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.



Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.





