ASCOLI SWING (CORD SET)

astro

GENERAL

LOCATION: Interior

CLASS: cULus (Class 1)

LOCATION RATING: Dry

DRIVER REQUIRED: Mains 120V
INSTALLATION ORIENTATION: Wall Mount

FITTING METHOD: Direct to Headboard

MAIN MATERIAL: Metal - Mild Steel

DIMENSIONS (mm): H:110 W:110 D:276

DIMENSIONS (inch): H:4.33 W:4.33 D:10.87

CUT OUT HOLE (mm/inch): RECESS DEPTH (mm/inch): FIRE RATING: -

CABLE LENGTH (mm/inch): 3000/118.11

GROSS WEIGHT (lb): 2.64

ADA COMPLIANT: Yes - if installed in compliance with

ADA 307.2, 308, 309.3, 309.4

IC RATING:

LAMP

LIGHT SOURCE: LED GU10 WATTAGE: 20W Max

RECOMMENDED LAMP: 6W Max LED GU10

LAMP INCLUDED: No MAXIMUM LAMP LENGTH (mm/inch): 57

LUMINOUS FLUX (Im):Lamp DependentCOLOUR TEMP (K):Lamp DependentCRI (Ra):Lamp DependentMACADAM ELLIPSE:Lamp Dependent

TILT ADJUSTABLE ANGLE (°): 90
ROTATION ADJUSTABLE ANGLE (°): 160

LIFETIME (hrs): Lamp Dependent BEAM ANGLE (°): Lamp Dependent

ELECTRICAL

SWITCHED: Yes

DIMMABLE: No

DIMMING METHOD:
SUPPLY FREQUENCY (Hz):
DRIVER/BALLAST VOLTAGE (V):
DRIVER LIFETIME (hrs): -

EFFICACY (Im/W): Lamp Dependent

ADDITIONAL INFORMATION:

SHADE INCLUDED: SHADE/DIFFUSER MATERIAL: SHADE/DIFFUSER FINISH -

F MARK: Suitable for mounting

on flammable materials



CODE: 1286104 FINISH: TEXTURED WHITE



CODE: 1286107 FINISH: MATT NICKEL



CODE: 1286108 FINISH: BRONZE

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED.
ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED
UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS,
AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY
RESERVED.

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.







