# ELBA 400 WALL

# astro

### GENERAL

LOCATION: Interior CLASS: cULus (Class 1)

LOCATION RATING: Dry

DRIVER REQUIRED: Mains 120V

INSTALLATION ORIENTATION: Wall Mount - Vertical FITTING METHOD: 4" Octagon Box

MAIN MATERIAL: Fabric

DIMENSIONS (mm): H: 400 W: 125 D: 100
DIMENSIONS (inch): H: 15.75 W: 4.92 D: 3.94

CUT OUT HOLE (mm/inch):

RECESS DEPTH (mm/inch):

FIRE RATING:

CABLE LENGTH (mm/inch):

GROSS WEIGHT (lb):

ADA COMPLIANT:

Yes

IC RATING:

-

# LAMP

LIGHT SOURCE: LED E26/Medium WATTAGE: 2 x 12W Max

RECOMMENDED LAMP: 12W Max LED E26/Medium

LAMP INCLUDED: No MAXIMUM LAMP LENGTH (mm/inch): 110/4.33

LUMINOUS FLUX (Im):Lamp DependentCOLOUR TEMP (K):Lamp DependentCRI (Ra):Lamp DependentMACADAM ELLIPSE:Lamp Dependent

TILT ADJUSTABLE ANGLE (°): ROTATION ADJUSTABLE ANGLE (°): -

LIFETIME (hrs): Lamp Dependent BEAM ANGLE (°): Lamp Dependent

#### **ELECTRICAL**

SWITCHED: DIMMABLE: Yes

DIMMING METHOD: Lamp Dependent


SUPPLY FREQUENCY (Hz): DRIVER/BALLAST VOLTAGE (V): DRIVER LIFETIME (hrs): -

EFFICACY (Im/W): Lamp Dependent

## ADDITIONAL INFORMATION:

SHADE INCLUDED: Yes
SHADE/DIFFUSER MATERIAL: SHADE/DIFFUSER FINISH F MARK: -







CODE: 1469006 FINISH: PUTTY FABRIC

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.



