TAIKO 400 astro

GENERAL

LOCATION: Interior

CLASS: cULus (Class 1)

LOCATION RATING: Dry

DRIVER REQUIRED: Mains 120V
INSTALLATION ORIENTATION: Ceiling Mount
FITTING METHOD: 4" Octagon Box
MAIN MATERIAL: Metal - Mild Steel
DIMENSIONS (mm): H: 150 Ø: 400
DIMENSIONS (inch): H: 5.91 Ø: 15.75

CUT OUT HOLE (mm/inch):

RECESS DEPTH (mm/inch):

FIRE RATING:

CABLE LENGTH (mm/inch):

GROSS WEIGHT (Ib):

10.25

ADA COMPLIANT: Yes - if installed in compliance

with ADA 307.4

IC RATING: -

LAMP

LIGHT SOURCE: LED E26/Medium WATTAGE: 3 x 12W Max

RECOMMENDED LAMP: 12W Max LED E26/Medium

LAMP INCLUDED: No
MAXIMUM LAMP LENGTH (mm/inch): 150/5.9

LUMINOUS FLUX (Im):Lamp DependentCOLOUR TEMP (K):Lamp DependentCRI (Ra):Lamp DependentMACADAM ELLIPSE:Lamp Dependent

TILT ADJUSTABLE ANGLE (°): ROTATION ADJUSTABLE ANGLE (°): -

LIFETIME (hrs): Lamp Dependent BEAM ANGLE (°): Lamp Dependent

ELECTRICAL

SWITCHED: No DIMMABLE: Yes

DIMMING METHOD: Lamp Dependent

SUPPLY FREQUENCY (Hz): DRIVER/BALLAST VOLTAGE (V): DRIVER LIFETIME (hrs): -

EFFICACY (Im/W): Lamp Dependent

ADDITIONAL INFORMATION:

SHADE INCLUDED: -

SHADE/DIFFUSER MATERIAL: Plastic SHADE/DIFFUSER FINISH Natural

F MARK: Suitable for mounting on flammable materials







CODE: 1456008 FINISH: MATT WHITE

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.





