Fuse 3 USB

astro

General

Location: Interior

Class: cULus (Class 1)

Location Rating: Dry

Driver Required: Mains 120V

Installation Orientation: Wall Mount - Horizontal or Vertical

Fitting Method: Included Junction Box

Main Material: Metal - Mild Steel

Dimensions (mm): H: 200 W: 75 D: 102

Dimensions (inch): H: 7.87 W: 2.95 D: 4.02

Cut Out Hole (mm/inch): L: 194 W: 67/L: 7.64 W: 2.64

Recess Depth (mm/inch): 70/2.76

Fire Rating: Cable Length (mm/inch): Gross Weight (lb): 2.86

Gross Weight (lb): 2.86

Ada Compliant: Yes

Ic Rating: IC Rated

Lamp

Light Source: High Power LED

Wattage: 3.3W

Lamp Included: Yes (Integral)

Maximum Lamp Length (mm/inch): Luminous Flux (lm): 141 2700 Colour Temp (K): 90 Cri (Ra): Macadam Ellipse: 3-Step 90 Tilt Adjustable Angle (°): Rotation Adjustable Angle (°): 330 Average Lifetime (hrs): 51000 Beam Angle (°): 18

Electrical

Switched: Yes

Dimmable: No

Dimming Method: Supply Frequency (Hz): 50-60

Driver/Ballast Voltage (V): 100-277

Driver Average Lifetime (hrs): 100000

Efficacy (Im/W): 43

USB Socket Output (V/A): 5/2.1

Additional Information:

Shade Included: Shade/Diffuser Material: Shade/Diffuser Finish: -

F Mark: Suitable for mounting on flammable materials



CODE: 1215086 FINISH: MATT WHITE



CODE: 1215087 FINISH: MATT BLACK



CODE: 1215088 FINISH: POLISHED CHROME



CODE: 1215089 FINISH: MATT NICKEL



CODE: 1215090 FINISH: BRONZE



CODE: 1215101 FINISH: MATT GOLD

To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under U.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

Product Elevations



Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.







