Ascoli Swing

astro

General

Location: Interior

Class: cULus (Class 1)

Location Rating: Dry

Driver Required: Mains 120V **Installation Orientation:** Wall Mount

Fitting Method: ½" Stub Mount or 4" Octagon Box

 Main Material:
 Metal - Mild Steel

 Dimensions (mm):
 H: 110 W: 110 D: 276

 Dimensions (inch):
 H: 4.33 W: 4.33 D: 10.87

Cut Out Hole (mm/inch):

Recess Depth (mm/inch):

Fire Rating:

Cable Length (mm/inch):

Gross Weight (lb):

2.65

Ada Compliant: Yes - if installed in compliance with ADA 307.2, 308, 309.3, 309.4

lc Rating: -

Lamp

Light Source:GU10Wattage:50W MaxLamp Included:NoMaximum Lamp Length (mm/inch):57/2.44

Luminous Flux (Im):Lamp DependentColour Temp (K):Lamp DependentCri (Ra):Lamp DependentMacadam Ellipse:Lamp Dependent

Tilt Adjustable Angle (°): 90
Rotation Adjustable Angle (°): 160

Average Lifetime (hrs): Lamp Dependent
Beam Angle (°): Lamp Dependent

Electrical

Switched: Yes
Dimmable: No
Dimming Method: Supply Frequency (Hz): Driver/Ballast Voltage (V): Driver Average Lifetime (hrs): -

Efficacy (Im/W): Lamp Dependent

Additional Information:

Shade Included: Shade/Diffuser Material: Shade/Diffuser Finish: -

F Mark: Suitable for mounting

on flammable materials







CODE: 1286069 FINISH: MATT NICKEL







CODE: 1286122 FINISH: MATT BLACK

To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under U.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

Product Elevations



Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.







