

Ginestra 300

astro

General

Location:	Interior
Class:	cULus (Class 1)
Location Rating:	Dry
Driver Required:	Mains 120V
Installation Orientation:	Ceiling Mount
Fitting Method:	4" Octagon Box
Main Material:	Metal - Mild Steel
Dimensions (mm):	H: 2058 Ø: 300
Dimensions (inch):	H: 81.02 Ø: 11.81
Cut Out Hole (mm/inch):	-
Recess Depth (mm/inch):	-
Fire Rating:	-
Cable Length (mm/inch):	1800/70.87
Gross Weight (lb):	5.32
Ada Compliant:	Yes - if installed in compliance with ADA 307.4
Ic Rating:	-

Lamp

Light Source:	E26/Medium
Wattage:	43W
Lamp Included:	No
Maximum Lamp Length (mm/inch):	145/5.71
Luminous Flux (lm):	Lamp Dependent
Colour Temp (K):	Lamp Dependent
Cri (Ra):	Lamp Dependent
Macadam Ellipse:	Lamp Dependent
Tilt Adjustable Angle (°):	-
Rotation Adjustable Angle (°):	-
Average Lifetime (hrs):	Lamp Dependent
Beam Angle (°):	Lamp Dependent

Electrical

Switched:	No
Dimmable:	Yes
Dimming Method:	Lamp Dependent
Supply Frequency (Hz):	-
Driver/Ballast Voltage (V):	-
Driver Average Lifetime (hrs):	-
Efficacy (lm/W):	Lamp Dependent

Additional Information:

Shade Included:	-
Shade/Diffuser Material:	-
Shade/Diffuser Finish:	-
F Mark:	-



CODE: 1361005
FINISH: MATT BLACK



CODE: 1361008
FINISH: MATT WHITE

To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under U.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

