Micro Recess Switched

astro

General

Driver Required:

Location:InteriorClass:cULus (Class I)Location Rating:Damp

Installation Orientation:Wall Mount - VerticalFitting Method:Included Junction BoxMain Material:Metal - Mild SteelDimensions (mm):D: 97 Ø: 80Dimensions (inch):D: 3.82 Ø: 3.15

Cut Out Hole (mm/inch): Ø: 70/2¾"

Recess Depth (mm/inch): 55/2.17

Fire Rating: -

Cable Length (mm/inch): Gross Weight (lb): 0.98

Ada Compliant: Yes - if installed in compliance with ADA 307.2, 308, 309.3, 309.4

Mains 120V

Ic Rating: IC Rated

Lamp

Light Source: High Power LED

Wattage: 3.2W

Lamp Included: Yes (Integral)

Maximum Lamp Length (mm/inch): Luminous Flux (Im): 196 Colour Temp (K): 2700 Cri (Ra): 90 Macadam Ellipse: 3-Step Tilt Adjustable Angle (°): 90 Rotation Adjustable Angle (°): 330 51000 Average Lifetime (hrs): 16 Beam Angle (°):

Electrical

Switched: Yes

Dimmable: No

Dimming Method:
Supply Frequency (Hz): 50-60

Driver/Ballast Voltage (V): 100-277

Driver Average Lifetime (hrs): 100000

Efficacy (Im/W): 61

Additional Information:

Shade Included:

Shade/Diffuser Material:PlasticShade/Diffuser Finish:Black

F Mark: To Be Advised



CODE: 1407016 FINISH: MATT WHITE



CODE: 1407017 FINISH: MATT BLACK



CODE: 1407018 FINISH: MATT NICKEL



CODE: 1407019 FINISH: BRONZE



CODE: 1407020 FINISH: MATT GOLD

To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under U.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

Product Elevations



Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.









