## Varenna Stadium 535 3000K Phase

astro

## General

Location: Class: Location Rating: Driver Required: Installation Orientation: Fitting Method: Main Material: Dimensions (mm): Dimensions (inch): Cut Out Hole (mm/inch): Recess Depth (mm/inch): Fire Rating: Cable Length (mm/inch): Gross Weight (lb): Ada Compliant:

Ic Rating:

### Lamp

Light Source:	LED Strip
Wattage:	43.8W
Lamp Included:	Yes (Integral)
Maximum Lamp Length (mm/inch):	-
Luminous Flux (Im):	2540
Colour Temp (K):	3000
Cri (Ra):	90
Macadam Ellipse:	2900-3000K
Tilt Adjustable Angle (°):	-
Rotation Adjustable Angle (°):	-
Average Lifetime (hrs):	53000
Beam Angle (°):	To Be Advised

#### Electrical

Switched:	No
Dimmable:	Yes
Dimming Method:	Phase - Leading & Trailing Edge
Supply Frequency (Hz):	50/60
Driver/Ballast Voltage (V):	120-277
Driver Average Lifetime (hrs):	50000
Efficacy (Im/W):	58

## Additional Information:

Shade Included:	-
Shade/Diffuser Material:	Glass
Shade/Diffuser Finish:	Sandblasted
F Mark:	-

Bathroom / Interior cULus (Class 1) Damp Mains 120V Wall Mount - Horizontal or Vertical Hookup with MC Whip Glass - Float H: 1070 W: 535 D: 50 H: 42.13 W: 21.06 D: 1.97

--To Be Advised Yes - if installed in compliance with ADA 307.2, 308, 309.3, 309.4



CODE: 1420025 FINISH: MIRROR

2540 2000 2000-3000K 30000 9 Be Advised

> To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under U.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

# **Product Elevations**

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

