

Baton Reader LED

astro

General

| | |
|---------------------------|--|
| Location: | Interior |
| Class: | cULus (Class I) |
| Location Rating: | Dry |
| Driver Required: | Mains 120V |
| Installation Orientation: | Wall Mount - Horizontal or Vertical |
| Fitting Method: | 4" Octagon Box with included Canopy Kit |
| Main Material: | Metal - Aluminium |
| Dimensions (mm): | H: 508 W: 90.5 D: 112.5 |
| Dimensions (inch): | H: 20 W: 3.56 D: 4.43 |
| Cut Out Hole (mm/inch): | - |
| Recess Depth (mm/inch): | - |
| Fire Rating: | - |
| Cable Length (mm/inch): | - |
| Gross Weight (lb): | 4.28 |
| Ada Compliant: | Yes - if installed in compliance with ADA 307.2, 308, 309.3, 309.4 |
| Ic Rating: | - |

Main Lamp

| | |
|--------------------------------|----------------|
| Light Source: | Mid-Power LED |
| Wattage: | 4.8W |
| Lamp Included: | Yes (Integral) |
| Maximum Lamp Length (mm/inch): | - |
| Luminous Flux (lm): | 181 |
| Colour Temp (K): | 2700 |
| Cri (Ra): | 90 |
| Macadam Ellipse: | 3-Step |
| Tilt Adjustable Angle (°): | - |
| Rotation Adjustable Angle (°): | - |
| Average Lifetime (hrs): | 54000 |
| Beam Angle (°): | 160.3 |

Secondary Lamp

| | |
|--------------------------------|----------------|
| Light Source: | High Powered |
| Wattage: | 4.8W |
| Lamp Included: | Yes (Integral) |
| Luminous Flux (lm): | 93 |
| Colour Temp (K): | 2700 |
| Cri (Ra): | 90 |
| Macadam Ellipse: | 3-Step |
| Tilt Adjustable Angle (°): | 180 |
| Rotation Adjustable Angle (°): | 180 |
| Average Lifetime (hrs): | 51000 |
| Beam Angle (°): | 23 |

Additional Information:

| | |
|--------------------------|---|
| Shade Included: | - |
| Shade/Diffuser Material: | - |
| Shade/Diffuser Finish: | - |
| F Mark: | - |



Code: 1475027
Finish: Matt Black



Code: 1475028
Finish: Matt Nickel

Main Lamp Electrical

| | |
|--------------------------------|---------|
| Switched: | Yes |
| Dimmable: | No |
| Dimming Method: | - |
| Supply Frequency (Hz): | 50-60 |
| Driver/Ballast Voltage (V): | 100-277 |
| Driver Average Lifetime (hrs): | 100000 |
| Efficacy (lm/W): | 38 |

Secondary Lamp Electrical

| | |
|--------------------------------|---------|
| Supply Frequency (Hz): | 50-60 |
| Driver/Ballast Voltage (V): | 100-277 |
| Driver Average Lifetime (hrs): | 100000 |
| Efficacy (lm/W): | 19 |

To Maintain This Product To Its Best Condition, Please View Our Care And Cleaning Guidelines On The Support Section Of The Astro Website.

Astro® Is A Registered Trademark Of Astro Lighting Limited. Astro Lighting's Fixture Designs And Imagery Are Protected Under U.s. And International Intellectual Property Laws, And All Rights To Such Designs And Imagery Are Expressly Reserved.

Product Elevations

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

