

General

| | |
|---------------------------|---|
| Location: | Bathroom |
| Class: | cULus (Class 1) |
| Location Rating: | Damp |
| Driver Required: | No |
| Installation Orientation: | Wall Mount - Horizontal or Vertical |
| Fitting Method: | Hookup with MC Whip |
| Main Material: | Glass - Float |
| Dimensions (mm): | H: 914.4 W: 609.6 D: 44 |
| Dimensions (inch): | H: 36 W: 24 D: 1.73 |
| Cut Out Hole (mm/inch): | - |
| Recess Depth (mm/inch): | - |
| Fire Rating: | - |
| Cable Length (mm/inch): | - |
| Gross Weight (lb): | 15.4 |
| Ada Compliant: | Yes - if installed in compliance with ADA 308, 309.3, 309.4 |
| Ic Rating: | - |

Lamp

| | |
|--------------------------------|----------------|
| Light Source: | LED Strip |
| Wattage: | 28.9W |
| Lamp Included: | Yes (Integral) |
| Maximum Lamp Length (mm/inch): | - |
| Luminous Flux (lm): | 703-762 |
| Colour Temp (K): | 2700-6000 |
| Cri (Ra): | 90 |
| Macadam Ellipse: | 6 Step |
| Tilt Adjustable Angle (°): | - |
| Rotation Adjustable Angle (°): | - |
| Average Lifetime (hrs): | 35000 |
| Beam Angle (°): | - |

Electrical

| | |
|--------------------------------|---------|
| Switched: | Yes |
| Dimmable: | No |
| Dimming Method: | - |
| Supply Frequency (Hz): | 50/60 |
| Driver/Ballast Voltage (V): | 120-277 |
| Driver Average Lifetime (hrs): | 50000 |
| Efficacy (lm/W): | 42-45 |

Additional Information:

| | |
|--------------------------|---------|
| Shade Included: | - |
| Shade/Diffuser Material: | Plastic |
| Shade/Diffuser Finish: | - |
| F Mark: | - |



Code: 1486009
Finish: Mirror Glass

To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under U.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

Product Elevations

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

