

General

Location:	Interior
Class:	cULus (Class I)
Location Rating:	Damp
Driver Required:	Mains 120V
Installation Orientation:	Ceiling & Wall Mount
Fitting Method:	4" Octagon Box
Main Material:	Glass - Pressed
Dimensions (mm):	D: 80 Ø: 155
Dimensions (inch):	D: 3.15 Ø: 6.10
Cut Out Hole (mm/inch):	-
Recess Depth (mm/inch):	-
Fire Rating:	-
Cable Length (mm/inch):	-
Gross Weight (lb):	4.26
Ada Compliant:	Yes - if installed in compliance with ADA 307.2
Ic Rating:	Non IC Rated

Lamp

Light Source:	LED Module
Wattage:	5.6W
Lamp Included:	Yes (Integral)
Maximum Lamp Length (mm/inch):	-
Luminous Flux (lm):	275
Colour Temp (K):	2700/3000/4000
Cri (Ra):	90
Macadam Ellipse:	SDCM<3
Tilt Adjustable Angle (°):	-
Rotation Adjustable Angle (°):	-
Average Lifetime (hrs):	72000
Beam Angle (°):	125.6

Electrical

Switched:	No
Dimmable:	Yes
Dimming Method:	Phase - Trailing Edge
Supply Frequency (Hz):	50/60
Driver/Ballast Voltage (V):	120
Driver Average Lifetime (hrs):	50000
Efficacy (lm/W):	49

Additional Information:

Shade Included:	-
Shade/Diffuser Material:	-
Shade/Diffuser Finish:	-
F Mark:	-



Code: 1523003
Finish: Matt White

To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under U.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

Product Elevations

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

