

Nomad Bollard 400

astro

General

Location:	Exterior
Class:	cULus (Class I)
Location Rating:	Wet
Driver Required:	Mains 120V
Installation Orientation:	Ground/Floor
Fitting Method:	-
Main Material:	Metal - Aluminium
Dimensions (mm):	H: 400 Ø: 150
Dimensions (inch):	H: 15.75 Ø: 5.91
Cut Out Hole (mm/inch):	-
Recess Depth (mm/inch):	120 / 4.72
Fire Rating:	-
Cable Length (mm/inch):	-
Gross Weight (lb):	6.2
Ada Compliant:	-
Ic Rating:	-

Lamp

Light Source:	High Power LED
Wattage:	12.5W
Lamp Included:	Yes (Integral)
Maximum Lamp Length (mm/inch):	-
Luminous Flux (lm):	210
Colour Temp (K):	2700
Cri (Ra):	90
Macadam Ellipse:	3-Step
Tilt Adjustable Angle (°):	-
Rotation Adjustable Angle (°):	-
Average Lifetime (hrs):	51000
Beam Angle (°):	73.7

Electrical

Switched:	No
Dimmable:	Yes
Dimming Method:	Phase - Leading & Trailing Edge
Supply Frequency (Hz):	50/60
Driver/Ballast Voltage (V):	120
Driver Average Lifetime (hrs):	50000
Efficacy (lm/W):	17

Additional Information:

Shade Included:	-
Shade/Diffuser Material:	-
Shade/Diffuser Finish:	-
F Mark:	-



Code: 1484012
Finish: Textured Black

To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under U.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

Product Elevations

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

